



VP80G

Single-direction vibratory plates

Efficient and easy to operate in compaction works

VP80 is available with two engine options, no matter which model you choose, VP80 is guaranteed with excellent driving experiences and the best compaction results. VP80's base plate is made of high quality and robust material to achieve longer service life. The improved design at the edge of the base plate made it even more suitable to work along the curbs. For transportation, VP80 can use large lifting eye or wide lifting handles. VP80, your choice of compaction in confined areas.

Highlights

- Sturdy and durable
- Control handle
- Optimally shaped base plate
- Low HAV (< 2.5 m/s²)

Technical Data

■ Mechanical - Output Details

Centrifugal force	4,496 lbf
Transmission	Centrifugal Clutch - V-belt
Area capacity	8,611.2 ft ² /h
Forward Running	1.4 - 1.6 fps
Gradeability	35.0 %
Vibrations (Hz)	115.0 Hz

■ Mechanical Details

Length Drawbar op. pos.	38.7 "
Length Baseplate	23.2 "

Width	17.7 "
Width Baseplate	17.7 "
Height	33.1 "
Operating weight	172.0 lb

■ Engine

Effective power	5.9 hp
Nominal Engine speed	3,550.0 1/min

■ Operating Fluids

Exciter oil volume	0.19 qt US
--------------------	------------